


TECHLINE® EZ QUICK INSTALL GUIDE

ON-SURFACE LAYOUT

LAYOUT TIPS AND RECOMMENDATIONS

Techline EZ can be installed on-surface or under mulch. Use the guidelines provided on the back to select which dripper flow rate and spacing to use and how long to run the system.



STEPS FOR CHOOSING AND APPLYING TECHLINE® EZ

PRODUCT SELECTION GUIDELINE CHARTS

GENERAL GUIDELINES	SHRUB & GROUNDCOVER		
	CLAY SOIL	LOAM SOIL	SANDY SOIL
DRIPPER FLOW	0.26 GPH	0.4 GPH	0.6 GPH
DRIPPER INTERVAL	18"	18"	12"
LATERAL (ROW) SPACING	18" - 24"	18" - 24"	16" - 20"
APPLICATION RATE (INCHES/HOUR)	.19 - .14	.29 - .21	.72 - .58
TIME TO APPLY ¼" OF WATER (MINUTES)	79 - 107	52 - 71	21 - 26

Following these maximum spacing guidelines, dripper flow selection can be increased if desired by the designer. 0.9 GPH flow rate available for areas requiring higher infiltration rates, such as coarse sandy soils.

MAXIMUM LENGTH OF A SINGLE LATERAL (FEET)

DRIPPER SPACING	6"		12"				18"				
	0.26	0.4	0.26	0.4	0.6	0.9	0.26	0.4	0.6	0.9	
Inlet Pressure ↑	15 psi	128	93	240	176	139	105	341	251	198	150
	25 psi	164	120	308	226	179	136	440	323	255	194
	35 psi	189	138	356	261	206	157	508	374	296	224
	45 psi	209	153	394	289	227	173	563	414	326	248


FLOW PER 100 FEET

DRIPPER SPACING	0.26 DRIPPER		0.4 DRIPPER		0.6 DRIPPER		0.9 DRIPPER	
	GPH	GPM	GPH	GPM	GPH	GPM	GPH	GPM
6"	52	0.87	80	1.33	Not Available	Not Available	Not Available	Not Available
12"	26	0.43	40	0.67	61	1.02	92	1.53
18"	17	0.28	26	0.44	41	0.68	61	1.02

THE TECHLINE EZ COIL LABEL


To make product identification easy, each Netafim coil has a bright colored label, which designates the flow rate, and a large graphic shape, which indicates dripper spacing. Selecting the coil with the right dripper spacing and the right flow rate is easy, even from a distance.

The 200', 250' and 300' coils include a quick reference for square feet of area covered and minutes to apply ½" of water based on the distance between laterals when the minimum pressure is 25 psi.



SHAPE	SPACING	COLOR	FLOW RATE
NO SHAPE	6" SPACING		0.26 GPH
	12" SPACING		0.4 GPH
	18" SPACING		0.6 GPH
	24" SPACING		0.9 GPH

12mm FITTINGS FOR TECHLINE EZ



NETAFIM USA
5470 E. HOME AVE.
FRESNO, CA 93727
CS 888 638 2346
F 800 695 4753
www.netafimusa.com

LTEZQI 11/10