



A compact valve box with 4 internal solenoid valves available to suit either 24Vac or 9Vdc latching irrigation controllers. Installation is easy and the eZyvalve4™ provides a trouble free way to distribute water in a micro irrigation system.

## Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilized materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non slip lid with o-ring seal and stainless steel screws.
- 3/4" MNPT threaded inlet and outlet connections.
- Patented (US patent 9936653) functionality.

## Applications

Landscape, home gardens, greenhouses and nurseries. Above or below ground installation.



eZyvalve4™ - 24 Vac



eZyvalve4™ - 9 Vdc Latch



## Performance Chart

Flow Rate (gpm)	Pressure Loss (psi)
3	5
4	9
5	14
6	20
7	27
8	34

## Ordering Information - eZyvalve4™

Type	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
eZyvalve4™ Valve Box 4 Solenoid Valves 3/4" NPT -24 Vac	16615	1	5	12.3
eZyvalve4™ Valve Box 4 Solenoid Valves 3/4" NPT 9 Vdc Latch	16635	1	5	12.3

## Ordering Information - eZyvalve4™ Repair Kits

Type	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
eZyvalve4™ 9 Vdc Solenoid Kit	16601	1	60	17.8
eZyvalve4™ Hardware Kit	16602	1	560	31.4
eZyvalve4™ 24 Vac Solenoid Kit	16603	1	60	17.8
eZyvalve4™ Diaphragm Kit (suits 24 Vac or 9 Vdc Solenoids)	16604	1	125	7.0

## Specifications

DIMENSIONS PACKAGED		CONNECTION TYPE	
HEIGHT	4.1 in	INLET	3/4" NPT
WIDTH	7.2 in		
DEPTH	7.2 in	OUTLET	3/4" NPT x 4 Outlets
WEIGHT (approx.) - 24 Vac	2 lbs 6 oz		
WEIGHT (approx.) - 9 Vdc	2 lbs 9 oz		

## OPERATING SPECIFICATIONS

FLOW	0.25 gpm - 8 gpm
PRESSURE - 24 Vac	3 psi - 180 psi
PRESSURE - 9 Vdc	3 psi - 108 psi
AMBIENT TEMPERATURE	35°F - 140°F
ELECTRICAL - 24 Vac	24 Vac, inrush current 291 mA, holding current 237 mA at 60 Hz
ELECTRICAL - 9 Vdc	9 Vdc, inrush current 1200 mA